



序号 No.	主 要 技 术 参 数 Main Technical Specification	型号 Type	
		TF-40.5/1250-20A	
电气参数 ELECTRIC RATINGS			
1	额定电压 Rated Voltage	kV	40.5
2	额定电流 Rated Current	A	1250
3	额定频率 Rated Frequency	Hz	50/60
4	额定短时（1 分钟）工频耐受电压 Rated Short-time(1min) Power-Frequency Withshand Voltage	kV	95
5	额定触头压力下限时的回路电阻 Circuit Resistance At Lowest Rated Contact Force	μ Ω	≤40
6	雷电冲击耐受电压 Lightning Impulse Withstand Voltage	kV	185
7	额定短时耐受电流 4 秒 Rated Short-time Withstand Current, 4s	kA	20
8	额定峰值耐受电流 Rated Peak Withstand Current	kA	50
9	额定短路关合电流 Rated Short-circuit Making Current	kA	50
10	额定有功负载开断电流 Rated Active Load Breaking Current	A	630
11	额定闭环开断电流 Rated Closed-loop Breaking Current	A	630
寿命 LIFE			
1	机械寿命 Mechanical Life	Times	10,000
2	储存时间 Storage Life	years	≥20
3	触头允许磨损厚度 Contacts Erosion Limit	mm	3
机械数据 MECHANICAL DATA			
1	触头自闭力 Contact Force From Atmosphere	N	130±50
2	触头反力 Counterforce of Contacts at Full Stroke	N	210±50
配套的真空开关设备应满足的机械参数 MECHANICAL DATA OF VACUUM SWITH EQUIPPED WITH THE INTERRUPTERS			
1	触头开距 Contact Stroke	mm	18±1
2	超行程 Overtrave	mm	3±1
3	平均分闸速度 Average Opening Speed	m/ s	1.6±0.2
4	平均合闸速度 Average closing speed	m/ s	0.8±0.2
5	触头合闸弹跳时间 Contact Bouncing Duration at Cosing Operation	ms	≤2
6	额定触头压力 Rated Added External Contactfinal Force	N	1000±100



TF-40.5/1250-25A

型负荷开关用真空灭弧室

Vacuum Interrupter For Load-Breaking Switch

