

Model NPS19-F

Piezoresistive OEM pressure sensor
Flush Diaphragm

Materontek
Sensing and Internet of Things

Features

- Piezoresistive pressure chip encapsulated in an oil-filled metal housing
- Measuring ranges from 100mbar to 40bar
- Gauge pressure, absolute pressure
- Accuracy: $\pm 0.25\%$ FSO(Typ.)
- Ø19mmx12.5mm
- Flush diaphragm structure



Application

- Hydraulic and pneumatic
- OEM
- Sanitary Industry
- Water treatment
- IoT pressure measurement

Technical data

| Performance | |
|-------------------------------------|--|
| Accuracy* | ±0.25 %FS(typ.), ±0.5 %FS(max.) |
| Linearity | ±0.2 %FS(typ.), ±0.3 %FS(max.) |
| Hysteresis | ±0.03 %FS(typ.), ±0.05 %FS(max.) |
| Repeatability | ±0.03 %FS(typ.), ±0.05 %FS(max.) |
| Operating temperature | -40 to 120 °C |
| Compensated temperature range | 0 to 60 °C(P≤0.35 bar), -10 to 70 °C(P>0.35 bar) |
| Temperature coefficient zero | ±0.75 %FS(typ.), ±1.5 %FS(max.) |
| Temperature coefficient sensitivity | ±0.75 %FS(typ.), ±1.5 %FS(max.) |
| Vibration | 10 g RMS(20 to 2000Hz) |
| Shock | 100 g(10ms) |
| Cycles | 10x10 ⁶ |
| Overpressure | 150 %FS |
| Long term stability | ±0.2 %FS(typ.) |

| Electrical @25°C | |
|-----------------------|--|
| Zero output | ±2 mV / V _S = 1.5 mA |
| Full scale output | 90 mV(typ.) , 150 mV(max.) / V _S = 1.5 mA |
| Excitation | 1 mA~2 mA |
| Bridge resistance | 2~8 kΩ |
| Insulation resistance | 100 MΩ@100VDC |

| Physical Specifications | |
|-------------------------|----------------------|
| Housing | 316L stainless steel |
| Diaphragm | 316L stainless steel |
| Oil Filling | Silicone oil |
| Weight | ~15g |

The listed specifications and dimensions are subject to change without prior notice

Model NPS19-F

Piezoresistive OEM pressure sensor
Flush Diaphragm


Materontek
Sensing and Internet of Things

Standard pressure range

| Code | Nominal pressure [bar] | Gauge | Sealed gauge | Absolute |
|------|------------------------|-------|--------------|----------|
| 01 | 0...0.1 | ✓ | | |
| 02 | 0...0.2 | ✓ | | |
| 03 | 0...0.35 | ✓ | ✓ | |
| 04 | 0...0.7 | ✓ | ✓ | |
| 05 | 0...1 | ✓ | ✓ | |
| 06 | 0...1.6 | ✓ | ✓ | |
| 07 | 0...2.5 | ✓ | ✓ | |
| 08 | 0...4 | ✓ | ✓ | |
| 09 | 0...6 | ✓ | ✓ | |
| 10 | 0...10 | ✓ | ✓ | |
| 11 | 0...16 | ✓ | ✓ | ✓ |
| 12 | 0...25 | ✓ | ✓ | ✓ |
| 13 | 0...40 | | ✓ | |

| Code | Nominal pressure [bar] | Gauge | Sealed gauge | Absolute |
|------|------------------------|-------|--------------|----------|
| 14 | -0.1...+0.1 | ✓ | | |
| 15 | -0.2...+0.2 | ✓ | | |
| 16 | -0.5...+0.5 | ✓ | | |
| 17 | -1...0 | ✓ | | |
| 18 | 0...-1 | ✓ | | |
| 19 | -1...+1 | ✓ | | |
| 20 | -1...+1.6 | ✓ | | |
| 21 | -1...+2.5 | ✓ | | |
| 22 | -1...+4 | ✓ | | |
| 23 | -1...+6 | ✓ | | |
| 24 | -1...+9 | ✓ | | |
| 25 | -1...+10 | ✓ | | |
| 26 | -1...+16 | ✓ | | |
| 27 | -1...+25 | ✓ | | |
| 28 | 0.8...2 | ✓ | | ✓ |

Dimensions (All dimensions in mm)



Ordering code

| Model | Range | Type | Output / Excitation | Electrical Connection | Compensation |
|----------------|-------------|-----------------------|----------------------------|--|---|
| NPS19-F | code | G gauge | 1 mV / 1.5 mA | F silicon rubber wires(L=100mm) | T with temperature compensated |
| | | S sealed gauge | 2 mV / DC 10V | P pins | NA without temperature compensated |
| | | A absolute | 3 0.5~4.5VDC / 5VDC | | |
| | | | 4 4~20mA / 10~30VDC | | |